
## PENNY BLENDS



## SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

| Wall      | Floor                         | Wet areas | Pools | Material |
|-----------|-------------------------------|-----------|-------|----------|
| Int / Ext | Residential / No <sup>1</sup> | Yes       | Yes   | Glass    |

<sup>1</sup> Penny Natureglass Opalo Black & Penny Natureglass Opalo White

## TECHNICAL CHARACTERISTICS

| Test<br>UNE-EN-ISO 10545-3<br>Water Absorption              | Test<br>UNE-EN-ISO-101-92=101<br>Surface hardness.<br>Mohs | Test<br>UNE-EN-ISO 10545-9<br>Resistance to<br>thermal shocks        | Test<br>UNE-EN-ISO<br>10545-12<br>Frost resistance                   | Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack |   |   |   |
|---|--|--|--|---|---|---|---|
|   |  |  |  | Domestic products   | Pool water additives                                | Low acid and alkalins                         | High acid and alkalins  |
| None  | 4 / 5¹   | Resistant  | Resistant  | GA  | GA  | GLA   | GHA   |
| Test<br>UNE-EN-ISO<br>10545-14<br>Resistance<br>to staining | Test<br>UNE-EN-ISO<br>10545-11=1997<br>Cracking            | DIN 51094<br>Colour Stability on<br>exposure to light and<br>UV rays | DCOF<br>Wet Dynamic Coefficient of Friction<br>ANSI A 137.1 Standard |   | DIN 51130:2004<br>SLIP Ressistance<br>wearing shoes | DIN 51097<br>SLIP Ressistance in<br>bare feet | Test UNE-ENV<br>12633:2003 (CTE) Anti<br>skid coefficient, suita-<br>ble for outdoor use and<br>swimming pools. |
| Class 5   | Resistant  | Resistant  | ≥ (  | ),42 <sup>1</sup>   | R11 <sup>1</sup>                                    | Class C <sup>1</sup>                          | Class 31  |

<sup>1</sup> Penny Almond Matte

## PACKING

| Sheet   Hoja             | 5,5 mm - 0.21″ Thickness | 287x284 mm - 11.299"x11.183" | 0,77 kg - 1.69 lb      |  |
|--------------------------|--------------------------|------------------------------|------------------------|--|
| Box   Caja               | 12 Sheets                | 0,98 m² - 10.54 sqft         | 9,39 kg - 20.7 lb      |  |
| Pallet   Palet           | 99 Boxes                 | 97,02 m² - 1044.31 sqft      | 941,44 kg - 2075.52 lb |  |
| Euro Pallet   Euro Palet | 54 Boxes                 | 52,82 m² - 568.54 sqft       | 530,86 kg - 1170.34 lb |  |

All ONIX 98 % recycled glass mosaics series are made of molten glass. Molten glass characteristics may include irregular edges and small variations in size. These characteristics are inherent to the product and to the standard production. The small size and shape variations can affect the grout joint appearance and enhance the natural aspect of these products.



98% Recycled Glass

🔵 Made in Spain

