



Product: 30 Inch Gas Range in Stainless Steel

Model Number: LRG3001U / LRG3001ULP

TECHNICAL DETAILS

Fuel Type	Natural Gas / LP Convertible
Electrical Requirements	120V
Circuit Breaker	20A
Frequency	60 Hz

BURNER PERFORMANCE

Total Burners	5
[1] Front Left (Single)	18,000 BTU
[2] Front Right (Single)	8,000 BTU
[3] Rear Left (Single)	4,000 BTU
[4] Rear Right (Single)	6,000 BTU
[5] Middle (Oval)	9,000 BTU
Tube Broil burner	10,000 BTU
U-shape burner (30" Oven)	18,500 BTU



FEATURES & BENEFITS

- High-Powered BTU Burners:** The high-powered 18,000 BTU burner provides fast, intense heat for creating large family meals and restaurant-quality dishes.
- Large Oven Capacity:** 4.55 cu. ft. oven capacity can accommodate multiple dishes at a time.
- Storage Space:** Storage drawer provides additional storage space for cooking trays and other kitchen utensils.
- Convection Fan:** Commercial convection fan provides controlled heat distribution for fast and efficient cooking.
- Even Heat Broiler:** Reflective gas tube broiler distributes heat evenly to sear your food and seal in the juices.
- Continuous Cast-Iron Grates:** Heavy-duty continuous cast-iron cooking grates that can handle any size cookware.
- Professional Knobs:** Black burner control knobs add style to the bold range design.
- Porcelain Spill Tray:** Single-piece black porcelain spill tray catches the mess and makes cleanup easy.
- Porcelain Interiors:** The gray porcelain oven interior adds a stylish touch and is easy to clean.

ACCESSORIES (NOT INCLUDED)

Liquid Propane Gas Conversion Kit	LPKLRG3001U
Wok Ring	WK01
Cast Iron Reversible Griddle	RG1022



WARRANTY: 2 YEARS PARTS AND LABOR





PRODUCT DIMENSIONS

Product Width	30"
Product height (from bottom to top of back splash)	36 5/8"-37 5/8"
Product height (from bottom to top of side panel)	36 1/8"-37 1/8"
Product depth (from back panel to bullnose)	27 1/2"
Product depth (from back panel to control board)	27 3/4"
Product depth (from back panel to side panel front)	24 3/4"
Depth of control panel (minimum)	2 1/4"
Depth of control panel (bullnose)	3 9/16"
Adjustable Legs	Not to Exceed 1"

REQUIRED CUTOUT SIZE

30 1/8" x 24 3/4" x 35 5/8 (+1")



NG: Input Pressure: 7 inches,
Output Pressure: 5 inches
LP: Input Pressure: 11 inches
Output Pressure: 10 inches
Size of Regulator: 1/2 inch

